

# DUCTILE IRON FITTINGS

## DPS (C900) PRODUCTS - DEEP, SLANT BELL DUCTILE IRON FITTINGS



<b>SIZES</b>	2 - 12" IPS, 4 - 24" DPS & 63 - 400MM DIN
<b>MATERIAL</b>	CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C153
<b>PRESSURE RATING</b>	250 PSI
<b>EPOXY COATING</b>	ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 10-12 MIL
<b>HARDWARE</b>	304 STAINLESS STEEL, OPTIONAL 316 STAINLESS STEEL
<b>BELL SOCKETS</b>	DEEP SLANTED BELL, ANSI/AWWA C116/A21.16-09, 4-LUGS TO ACCOMMODATE JOINT RESTRAINTS & ADDITIONAL FITTINGS
<b>GASKETS</b>	HIGH GRADE EPDM RUBBER ANSI/AWWA C111/A21.11, RIB-ENFORCED DESIGN
<b>DEFLECTION</b>	5 DEGREES
<b>INSTALLATION</b>	PER IPS, DPS & DIN PIPE STANDARDS

### SPECIFICATION

Fittings shall be ductile iron, slanted, deep bell, gasket style made in accordance with ASTM A536, Grade 65-45-12 and AWWA C153. Fittings shall have four lugs to accommodate joint restraints and other fittings. Bell section shall allow 5-degree freedom of pipe deflection within the bell end. All gaskets shall be manufactured of high grade EPDM rubber and shall be rib-enforced "U-Cup" design to seal and assist in restraining pipe at all pressures. Epoxy Coating on interior and exterior surfaces of fittings shall be fusion bonded epoxy, 10-12 mil thickness. The epoxy coated fittings shall pass 90-Day immersion tests per CSA Z245.20-98. All IPS, DPS and DIN Metric fittings shall have FBE coating as standard finish. All fittings shall be manufactured by Leemco, Inc., U.S.A.

LEEMCO HAS A LARGE VARIETY OF  
FITTINGS AND VALVE ACCESSORIES.  
PLEASE VISIT OUR WEBSITE AT [LEEMCO.COM](http://LEEMCO.COM)



Leemco, Inc.  
360 S. Mount Vernon Ave.  
Colton, CA 92324  
Ph: (909) 422-0088 Fx: (909) 422-0086  
[leemco.com](http://leemco.com)