

MAINLINE RESILIENT WEDGE GATE VALVES

IPS PRODUCTS - LMV-SERIES

THREADED MAINLINE GATE VALVES (FPT X FPT) FOR IPS & DPS PLASTIC PIPE



LMV-TT (IPS & DPS) SERIES (FPT X FPT)		
MODEL #	FPT	FPT
LMV-11TT	2"	2"
LMV-22TT	2.5"	2.5"
LMV-33TT	3"	3"
LMV-44TT	4"	4"

250 PSI DUCTILE IRON BODY GATE VALVES

- FPT X FPT
- Bolted Bonnet
- Non-Rising Stem
- Resilient Wedge
- Conforms to AWWA C515 Standards
- 10-Year Warranty

MATERIAL	CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C515
PRESSURE RATING	250 PSI
EPOXY COATING	AWWA C550, NSF 61 & CSA Z245.20-98, 12-14 MIL
WEDGE	DUCTILE IRON ASTM A-536, EPDM RUBBER, ASTM D429
GASKETS/O-RINGS	HIGH GRADE EPDM RUBBER
INSTALLATION	PER IPS & DPS PIPE STANDARDS

SPECIFICATION

All mainline valves shall be resilient wedge and conform to AWWA C515 standards. Material shall be ductile iron per ASTM A536, Grade 65-45-12. Epoxy coating on all interior and exterior surfaces shall be fusion bonded epoxy, 12-14 mil thickness. The epoxy coating shall pass 90-Day immersion tests per CSA Z245.20-98. Valves shall have a shroud around the 2" operating nut to accept IPS PVC sleeve which provides dirt-free access to actuate the valve. All mainline valves shall be manufactured by Leemco, Inc., U.S.A.

LEEMCO HAS A LARGE VARIETY OF VALVE
ACCESSORIES.
PLEASE VISIT OUR WEBSITE AT LEEMCO.COM

 **Leemco, Inc.**
Piping Solutions

Leemco, Inc.
360 S. Mount Vernon Ave.
Colton, CA 92324
Ph: (909) 422-0088 Fx: (909) 422-0086
leemco.com