

LATERAL CONNECTION SYSTEM

DIN PRODUCTS - LV-SERIES ANGLE VALVES



LATERAL TEE

DLT-92T (90MM)
DLT-112T (110MM)
DLT-162T (160MM)
DLT-202T (200MM)
DLT-222T (225MM)
DLT-252T (250MM)
DLT-282T (280MM)
DLT-322T (315MM)



RSLs-SERIES SINGLE SS STRAP SADDLE

RSLS-300 (90MM)
RSLS-400 (110MM)
RSLS-600 (160MM)
RSLS-800 (200MM)
RSLS-1000 (250MM)
RSLS-1200 (315MM)



RDLS-SERIES DOUBLE SS STRAP SADDLE

RDLS-300 (90MM)
RDLS-400 (110MM)
RDLS-600 (160MM)
RDLS-800 (200MM)
RDLS-1000 (250MM)
RDLS-1200 (315MM)



LX-SERIES EXTENSIONS

LX-6 (6")
LX-12 (12")



LMN-SERIES (SPIGOT X MPT) OUTLET ADAPTER

DLMN-65 (63MM X 1")
DLMN-66 (63MM X 1.25")
DLMN-77 (63MM X 1.5")
DLMN-99 (63MM X 2")



LMA-200 FMA-200

LFA-200 LFA-300

INLET ADAPTERS

DLMA-6 (2 BELL X 63MM)
DLMA-200BSP (2 BELL X 2 BSP)
DL-263SB (2 SPIG X 63MM BELL)
L90-63SB (2 SPIG X 63MM BELL)
90 EL
DLT90-63 (2 SPIG X 63MM BELL)
LAT 90 EL
DLHDP-263 (2 SPIG X 63 FLARE)

MATERIAL	CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C153
PRESSURE RATING	250 PSI
EPOXY COATING	ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 10-12 MIL
HARDWARE	304 STAINLESS STEEL, OPTIONAL 316 STAINLESS STEEL
GASKETS	HIGH GRADE EPDM RUBBER ANSI/AWWA C111/A21.11, RIB-ENFORCED DESIGN
INSTALLATION	PER DIN PIPE STANDARDS

SPECIFICATION

All lateral connection products shall be made with ductile iron per ASTM A536, Grade 65-45-12. All exterior and interior surfaces shall be fusion bonded epoxy coating, 10-12 mil thickness. All lateral connection products shall be manufactured by Leemco, Inc., U.S.A.

LEEMCO HAS A LARGE VARIETY OF FITTINGS AND VALVE ACCESSORIES.

PLEASE REFER TO OUR IPS PRICE LISTS FOR AVAILABLE MODELS AND SIZES.



Leemco, Inc.
360 S. Mount Vernon Ave.
Colton, CA 92324
Ph: (909) 422-0088 Fx: (909) 422-0086
leemco.com