


SADDLES

DIN PRODUCTS - SADDLES



RSST-Series (IPS & DIN)



RSDT-Series (IPS & DIN)



RSLs-Series (IPS & DIN)



RDLS-Series (IPS & DIN)

SADDLE BODIES	CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C153
STAINLESS STRAP	304 STAINLESS STEEL PER ASTM A240, PACIFIED FOR CORROSION RESISTANCE
HARDWARE	304 STAINLESS STEEL, OPTIONAL 316 STAINLESS STEEL
PRESSURE RATING	250 PSI
EPOXY COATING	ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 10-12 MIL
GASKETS	HIGH GRADE EPDM RUBBER ANSI/AWWA C111/A21.11
INSTALLATION	PER IPS & DIN PIPE STANDARDS

SPECIFICATION

Saddle bodies shall be constructed of ductile iron per ASTM A536, Grade 65-45-12, AWWA C153 standards. RSST, RSDT, RSLs and RDLS-Series straps, and hardware shall be 304 stainless steel. Saddle gaskets shall be constructed of high grade EPDM rubber per ANSI/AWWA C111/A21.11 standards. Epoxy coating shall be 10-12MM thick to protect against corrosive soils. 2" LAT Bell outlet accepts Leemco lateral connections. All saddles shall be manufactured by Leemco, Inc., U.S.A.

LEEMCO HAS A LARGE VARIETY OF SADDLES AND ACCESSORIES.

PLEASE VISIT OUR WEBSITE AT LEEMCO.COM



Leemco, Inc.
360 S. Mount Vernon Ave.
Colton, CA 92324
Ph: (909) 422-0088 Fx: (909) 422-0086
leemco.com