

SADDLES

IPS PRODUCTS - STAINLESS STEEL SADDLES



IPS MODELS

MODEL #	DESCRIPTION
RSST-215	2 x 1.5 FPT SS Saddle
RSST-215A	2 x 1.5 ACME SS Saddle
RSST-2515	2.5 x 1.5 FPT SS Saddle
RSST-2515A	2.5 x 1.5 ACME SS Saddle
RSST-315	3 x 1.5 FPT SS Saddle
RSST-315A	3 x 1.5 ACME SS Saddle

METRIC MODELS

MODEL #	DESCRIPTION
RSST-6315	63mm x 1-1/2" FPT SS Saddle
RSST-6315A	63mm x 1-1/2" ACME SS Saddle
RSST-6315B	63mm x 1-1/2" BSP SS Saddle
RSST-9015	90mm x 1-1/2" FPT SS Saddle
RSST-9015A	90mm x 1-1/2" ACME SS Saddle
RSST-9015B	90mm x 1-1/2" BSP SS Saddle

SADDLE BODIES	316 STAINLESS STEEL PER ASTM A240, PACIFIED FOR CORROSION RESISTANCE
HARDWARE	316 STAINLESS STEEL PER ASTM A240, PACIFIED FOR CORROSION RESISTANCE
PRESSURE RATING	250 PSI
GASKETS	HIGH GRADE EPDM RUBBER PER ANSI/AWWA C111/A21.11
SIZES	2", 2-1/2", 3" IPS SIZES (1-1/2" FPT OR 1-1/2" ACME OUTLETS)
SIZES	63MM & 90MM SIZES (1-1/2" FPT, ACME OR BSP OUTLETS)
INSTALLATION	PER IPS & METRIC PIPE STANDARDS

SPECIFICATION

Saddle construction shall be made of 316 stainless steel. Saddle shall have a round anti-rotation device that is built within the saddle and made to insert into a 1-1/2" cored out hole. Saddles shall have a built-on joint restraint system. Gasket seal shall be made of high grade EPDM rubber per ANSI/AWWA C111/A21.11. All saddles shall be manufactured by Leemco, Inc., U.S.A.

LEEMCO HAS A LARGE VARIETY OF SADDLES
AND ACCESSORIES.

PLEASE VISIT OUR WEBSITE AT LEEMCO.COM



Leemco, Inc.
360 S. Mount Vernon Ave.
Colton, CA 92324
Ph: (909) 422-0088 Fx: (909) 422-0086
leemco.com