

DUCTILE IRON VALVE BOX (FOR QUICK COUPLING VALVES)

IPS PRODUCTS - QUICK COUPLING VALVE CONNECTION

CAT. A
DUCTILE IRON VALVE BOX



MODEL #	LVB-12R
MATERIAL	CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C153
PRESSURE RATING	250 PSI
EPOXY COATING	ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 12-14 MIL
QCV STABILIZER	304 STAINLESS STEEL PLATE
BALL VALVE	1" FPT, 304 STAINLESS STEEL, FULL PORT, 1000 PSI, WATER, OIL & GAS (WOG)
QCV ASSEMBLY	1" MPT, 304 STAINLESS STEEL
LID REMOVAL TOOL	304 STAINLESS STEEL
WEIGHT	75 LB; 34 KG

SPECIFICATION

All quick coupling valves will be installed inside the Leemco LVB-12R ductile iron valve box. Valve box body and lid is constructed of Class 350 ductile iron per ASTM A536, Grade 65-45-12, AWWA C153 standards. The ductile iron body and lid have a FBE (fusion-bonded-epoxy) coating, ANSI/AWWA C116/A21.16-09, NSF 61 and CSA Z245.20-98, 12-14 MIL. All connection fittings, ball valve and lid removal tool are constructed of 304 stainless steel. All valve boxes shall be manufactured by Leemco, Inc. U.S.A.

LEEMCO HAS A LARGE VARIETY OF
FITTINGS AND VALVE ACCESSORIES.
PLEASE VISIT OUR WEBSITE AT LEEMCO.COM



Leemco, Inc.
360 S. Mount Vernon Ave.
Colton, CA 92324
Ph: (909) 422-0088 Fx: (909) 422-0086
leemco.com